

V05



The V05 electric locks are suitable for doors and pedestrian gates and are interchangeable with the most common electric locks already installed. The characteristics and finish make the painted versions ideal for inside wooden doors; the galvanized versions are best for outside metal doors and gates.

- **Installation:** horizontal.
- **Backset:** adjustable from 50 to 80 mm, by means of a simple operation with the Allen key supplied.
- **Double replaceable coil:** which distributes the load uniformly and ensures a long working life.
- **Voltage:** [standard 12V AC \(on request 12V DC; 24V AC or DC\)](#).
- **Case:** one-piece steel.
- **Cover:** steel.
- **Handle:** nylon, and nylon cylinder ring nut.
- **Latch:** solid brass, self-locking with the device locked.
- **Ejector:** nickel-plated steel, incorporated into the latch.
- **Cylinders:** solid brass, fixed internal, fixed or loose external.
- **Keys:** supplied with 3 Viro profile nickel-plated brass keys.
 - Versions available with [universal profile keys](#) to replace the most common electric locks already installed without the need to withdraw keys in use. ([Cylinders can be re-keyed with keying kit](#)).
- **Mechanism:**
 - brass pins;
 - mushroom brass counterpins, [pick-resistant](#);
 - phosphor bronze pin springs.
- **Striker:** steel, [adjustable height](#) to compensate for any vertical adjustment between the lock and the striker (caused by weather changes). Self-lubricating nylon support in contact with the ejector.
- **Supplied with:** steel striker, brass cylinder ring nut (for versions with loose external cylinder), oval brass escutcheon (for painted versions with fixed external cylinder), [roof-plate including striker plate \(for galvanized versions\)](#), Allen key for backset adjustment and fixing screws.
- **Packaging:** single box.
- **On request:**
 - available [anthracite metallic painted versions](#), add the required color code **.469** to the item code.

[Special visual packs.](#)

[All special executions are possible for the cylinder.](#)




METALLISED BRONZE PAINTED VERSIONS



Item No.		Adjustable backset mm E	Lock dimensions mm	Internal cylinder (fixed) Item No.	External cylinder (fixed) Item No.	External cylinder (loose) Item No.	Unit weight g
1.7962.712.1	right	50 ÷ 80	127.5 x 103.5	791	-	712	1430
1.7962.712.2	left	50 ÷ 80	127.5 x 103.5	791	-	712	1430

For versions with Universal profile keys the item code should be followed by: **.UN**.



FULLY GALVANIZED VERSIONS or ANTHRACITE METALLIC PAINTED WITH GALVANIZED BASE
with galvanized (item 8992.0600) or anthracite metallic painted (item 8992.0600.469) steel roof-plate and striker plate.



Item No.		Adjustable backset mm E	Lock dimensions mm	Internal cylinder (fixed) Item No.	External cylinder (fixed) Item No.	External cylinder (loose) Item No.	Unit weight g
1.7992.794.1	right	50 ÷ 80	127.5 x 103.5	791	794	-	2100
1.7992.794.2	left	50 ÷ 80	127.5 x 103.5	791	794	-	2100

For versions with Universal profile keys the item code should be followed by: **.UN**.

