

ELS-SB200

SOLENOID BOLT [MONITORED]

12/24VDC



OPERATING VOLTAGE:	12/24VDC
CURRENT DRAW:	0.35 AMPS @ 12VDC 0.17 AMPS @ 24VDC
OPERATION:	FAIL-SAFE [UNLOCKED]
HOLDING FORCE:	UP TO 1000lbs/450kgs
DIMENSIONS:	212 x 35 x 45mm
BOLT:	14mm DIAMETER x 16mm THROW
EXTERNAL USE:	NO
FINISH:	STAINLESS STEEL FACEPLATE
APPLICATION:	TIMBER METAL OR GLASS DOORS
MONITORING:	YES - DUAL
INSIDE:	PRESS TO EXIT OR SIMILAR
OUTSIDE:	KEYPAD OR SIMILAR
FIXING:	HORIZONTAL OR VERTICAL
HOUSING AVAILABLE:	YES - SURFACE
FEATURES:	SUITABLE FOR DOUBLE ACTION DOORS

Models

ELS-SB200
ELS-SB260
SURFACE HOUSING
ELS-SB200-SUR

Contact

**ELECTRIC LOCKING
SYSTEMS LIMITED**



sales@electriclock.co.uk

www.electriclock.co.uk