

**ASL950M1** - BE-Tech WALL READER (BE-Tech)

- 12v DC proximity wall reader
- Typical reading range up to 40mm
- Surface mounting
- Visual and audible Access Approved/Denied indication
- Dimensions 85 x 110 x 30mm

**ASL950M1W** - SMARTLOCK WALL READER (SmartLock)

- 12v DC proximity wall reader
- Typical reading range 40mm
- Surface mounting
- Protection class IP67
- Visual and audible Access Approved/Denied indication
- Operating temperature -40°C to +55°C
- Dimensions 40 x 110 x 30mm

**ASL95BASE** - SMARTLOCK WIRELESS HUB

- Connection using USB and Ethernet
- Frequency 433 MHz
- Supplied with 230v AC / 12v DC power supply unit
- Supplied complete with fixing brackets

**ASL1100** - BE-Tech LOCKER LOCK - PROXIMITY

- The battery-operated proximity locker lock
- Easy to programme for multi-users
- Typical reading range up to 40mm
- Battery life up to 15,000 activations
- Surface mounted with external and internal element for doors 12 - 2mm thick
- 2 x 1.5 AAA batteries

**ASL1800** - LOCKER LOCK - DIGITAL

- The battery-operated PinCode locker lock
- Easy to programme for multi-users
- 4-9 digit code
- Complete with 3 cam positions
- 2 x 1.5 AAA batteries



CARDS & TOKENS

- Mifare technology
- Full colour card printing option
- Wrist bands and fobs also available

**ASL961** - HAND HELD PROGRAMMER

- Battery operated PinCode Terminal is integrated wirelessly with the door locks
- Used at each door to programme and audit locks
- Dimensions 155 x 80 x 30mm

**ASL960** - USB CARD WRITER

- USB connection to main computer running system software
- Read/Write card activation
- Powered over USB port
- Dimensions 115 x 75 x 20mm

**ASL950** - CONTROL BOX

- 230v 3A power supply
- Contains control board to activate door(s)
- Dimensions 355 x 320 x 85mm

**ASL962** - BE-Tech SOFTWARE

- Windows™ based software
- PMS interface

**ASL961** - ENERGY SAVER

- 190 - 365v AC
- 16A load current
- 10°C - 60°C operating temperature
- Egress time delay 10-30 seconds
- Dimensions 86 x 86 x 44mm